



Accessing Source Code Files Using REST

Version 2024.1
2024-05-02

Accessing Source Code Files Using REST

InterSystems IRIS Data Platform Version 2024.1 2024-05-02

Copyright © 2024 InterSystems Corporation

All rights reserved.

InterSystems®, HealthShare Care Community®, HealthShare Unified Care Record®, IntegratedML®, InterSystems Caché®, InterSystems Ensemble®, InterSystems HealthShare®, InterSystems IRIS®, and TrakCare are registered trademarks of InterSystems Corporation. HealthShare® CMS Solution Pack™ HealthShare® Health Connect Cloud™, InterSystems IRIS for Health™, InterSystems Supply Chain Orchestrator™, and InterSystems TotalView™ For Asset Management are trademarks of InterSystems Corporation. TrakCare is a registered trademark in Australia and the European Union.

All other brand or product names used herein are trademarks or registered trademarks of their respective companies or organizations.

This document contains trade secret and confidential information which is the property of InterSystems Corporation, One Memorial Drive, Cambridge, MA 02142, or its affiliates, and is furnished for the sole purpose of the operation and maintenance of the products of InterSystems Corporation. No part of this publication is to be used for any other purpose, and this publication is not to be reproduced, copied, disclosed, transmitted, stored in a retrieval system or translated into any human or computer language, in any form, by any means, in whole or in part, without the express prior written consent of InterSystems Corporation.

The copying, use and disposition of this document and the software programs described herein is prohibited except to the limited extent set forth in the standard software license agreement(s) of InterSystems Corporation covering such programs and related documentation. InterSystems Corporation makes no representations and warranties concerning such software programs other than those set forth in such standard software license agreement(s). In addition, the liability of InterSystems Corporation for any losses or damages relating to or arising out of the use of such software programs is limited in the manner set forth in such standard software license agreement(s).

THE FOREGOING IS A GENERAL SUMMARY OF THE RESTRICTIONS AND LIMITATIONS IMPOSED BY INTERSYSTEMS CORPORATION ON THE USE OF, AND LIABILITY ARISING FROM, ITS COMPUTER SOFTWARE. FOR COMPLETE INFORMATION REFERENCE SHOULD BE MADE TO THE STANDARD SOFTWARE LICENSE AGREEMENT(S) OF INTERSYSTEMS CORPORATION, COPIES OF WHICH WILL BE MADE AVAILABLE UPON REQUEST.

InterSystems Corporation disclaims responsibility for errors which may appear in this document, and it reserves the right, in its sole discretion and without notice, to make substitutions and modifications in the products and practices described in this document.

For Support questions about any InterSystems products, contact:

InterSystems Worldwide Response Center (WRC)

Tel: +1-617-621-0700

Tel: +44 (0) 844 854 2917

Email: support@InterSystems.com

Table of Contents

1 Introduction to the InterSystems IRIS Source Code File REST API	1
2 Source Code File REST API Tutorial	3
2.1 API Basics	3
2.2 Getting Information about the Server	4
2.3 Getting the Source Code in a Namespace	5
2.4 Creating a New File in a Namespace or Updating an Existing File	6
2.5 Compiling a File	7
2.6 Deleting a File	7
2.7 Performing an SQL Query	8
3 Source Code File REST API Reference	11
3.1 GetServer	11
3.1.1 URL	11
3.1.2 JSON Messages	11
3.1.3 HTTP Return Codes	12
3.2 HeadServer	12
3.2.1 URL	12
3.2.2 JSON Messages	12
3.2.3 HTTP Return Codes	12
3.3 GetJobs	12
3.3.1 URL	12
3.3.2 JSON Messages	12
3.3.3 HTTP Return Codes	13
3.4 GetMetaData	13
3.4.1 URL	13
3.4.2 HTTP Return Codes	14
3.5 GetCSPApps	14
3.5.1 URL	14
3.5.2 URL Parameters	14
3.5.3 JSON Messages	14
3.5.4 HTTP Return Codes	15
3.6 GetNamespace	16
3.6.1 URL	16
3.6.2 JSON Messages	16
3.6.3 HTTP Return Codes	16
3.7 GetDocNames	17
3.7.1 URL	17
3.7.2 URL Parameters	17
3.7.3 JSON Messages	17
3.7.4 HTTP Return Codes	18
3.8 GetModifiedDocNames	18
3.8.1 URL	18
3.8.2 JSON Messages	19
3.8.3 HTTP Return Codes	19
3.9 PutDoc	19
3.9.1 URL and Input JSON Message	19
3.9.2 URL Parameters	20

3.9.3 HTTP Headers	20
3.9.4 JSON Messages	20
3.9.5 HTTP Return Codes	20
3.10 GetDoc	21
3.10.1 URL	21
3.10.2 URL Parameters	21
3.10.3 HTTP Headers	22
3.10.4 JSON Messages	22
3.10.5 HTTP Return Codes	22
3.11 DeleteDoc	23
3.11.1 URL	23
3.11.2 JSON Messages	23
3.11.3 HTTP Return Codes	24
3.12 HeadDoc	24
3.12.1 URL	24
3.12.2 HTTP Return Codes	24
3.13 GetDocs	24
3.13.1 URL	24
3.13.2 JSON Messages	25
3.13.3 HTTP Return Codes	25
3.14 DeleteDocs	25
3.14.1 URL	25
3.14.2 JSON Messages	25
3.14.3 HTTP Return Codes	26
3.15 Compile	26
3.15.1 URL	26
3.15.2 URL Parameters	26
3.15.3 JSON Messages	26
3.15.4 HTTP Return Codes	27
3.16 Index	27
3.16.1 URL	27
3.16.2 JSON Messages	28
3.16.3 HTTP Return Codes	29
3.17 Query	29
3.17.1 URL	29
3.17.2 JSON Messages	29
3.17.3 HTTP Return Codes	30
3.18 Search	30
3.18.1 URL	30
3.18.2 URL Parameters	30
3.18.3 JSON Messages	30
3.18.4 HTTP Return Codes	31
3.19 GetEnsClassType	31
3.19.1 URL	31
3.19.2 JSON Messages	32
3.19.3 HTTP Return Codes	32
3.20 GetAdpInputOutputClass	32
3.20.1 URL	32
3.20.2 JSON Messages	33
3.20.3 HTTP Return Codes	33

1

Introduction to the InterSystems IRIS Source Code File REST API

This REST API provides access to InterSystems IRIS® data platform source code files. Our VS Code - ObjectScript IDE uses the API to perform the actions needed to access InterSystems IRIS code files, and you can use the API in your own code. These actions include:

- Getting the namespaces available on an InterSystems IRIS instance
- Finding the class definitions and routines defined in a namespace
- Getting the text definitions of the classes and routines
- Updating a class definition or routine
- Creating a new class definition or routine
- Deleting a class definition or routine
- Compiling an InterSystems IRIS class or routine
- Discovering properties of the InterSystems IRIS environment by performing SQL queries on tables

These actions provide the mechanisms to access InterSystems IRIS source code files. In order to create an InterSystems IRIS development environment, you should understand this API and have a comprehensive understanding of how the InterSystems IRIS source code files are used within InterSystems IRIS.

This is a special-purpose API. If you are creating a development environment or working on a similar application, such as a class browser, you may find this API useful. But, it is not a general-purpose REST API to access InterSystems IRIS objects.

This document describes versions 1 and 2 of the InterSystems IRIS Source Code File REST API. Future releases of InterSystems IRIS may support higher versions of this REST API that provide additional calls, but you will always be able to call the earlier versions. The APIs for version 1 include `/v1/` in the URL and the APIs for version 2 include `/v2/`. You can find out the version of this API that is provided by InterSystems IRIS by calling the [GetServer](#) method.

The following describes the major capabilities of the API and the methods that provide them:

- Getting information about the server environment:
 - [GetServer](#) method provides the important information about the server including the namespaces on the server.
 - [GetNamespace](#) method provides additional information about the specified namespace. It includes the list of databases that are mapped to the namespace.

- [HeadServer](#) method provides header information about the server. You can call HeadServer to check if the server is available.
- [GetJobs](#) method provides information about the jobs running in InterSystems IRIS.
- [GetCSPApps](#) method provides information about the web applications defined by the server. These applications provide access to InterSystems IRIS.
- Getting information about source code files:
 - [GetDocNames](#) method provides the names of the source code files in the namespace. You can optionally limit the files to a specific category of files or with a specific file type.
 - [GetModifiedDocNames](#) method provides the same names as GetDocNames, but additionally provides a hash for the database state. If you keep a local copy of the file, you can call GetModifiedDocNames and see if the document has changed since you last retrieved it.
 - [GetDoc](#) method gets the contents of the specified source code file. You can optionally use the ETAG and If-None-Match headers to only get the contents of the source code file if it has changed since the previous time you retrieved it.
 - [GetDocs](#) method gets the contents of the specified files.
 - [Index](#) method provides some key properties of the class definitions in the namespace. Your application can use this information to select the class definitions to access.
 - [HeadDoc](#) method provides header information about source code files.
- Creating, updating, and deleting source code files
 - [PutDoc](#) method updates an existing source code file, or, if the file does not exist, creates a new source code file.
 - [DeleteDoc](#) method deletes the specified source code file.
 - [DeleteDocs](#) method deletes the specified list of source code files.
- Compiling source code files
 - [Compile](#) method compiles the source code file.
- Performing SQL queries to get information from InterSystems IRIS tables
 - [Query](#) method performs an SQL query on any InterSystems IRIS database.
- Searching in source code files
 - [Search](#) method searches source code files in the InterSystems IRIS database.
- Special calls for dealing with Ensemble classes
 - [GetEnsClassType](#) method returns the class type for Ensemble objects.
 - [GetAdpInputOutputClass](#) method returns the input and output adapter class for production adapters.

2

Source Code File REST API Tutorial

This page provides a brief tutorial that demonstrates how to use the InterSystems IRIS® data platform Source Code File REST API by a series of examples.

2.1 API Basics

This API gives you access to InterSystems IRIS source code files.

To call an API method, you need to know the following:

- HTTP method—which is one of the following: GET, POST, PUT, DELETE, or HEAD.
- HTTP headers—provide context information for the call. The HEADERS used in this API include:
 - Authorization, which provides access to the server. Unless you have installed your server with minimal security, you need to provide a username and password to access the API.
 - Content-Type `application/json`, which specifies that the inbound payload is provided in JSON. You must specify this header for all POST and PUT methods.
 - If-None-Match, which allows a GetDoc or PutDoc call to check if the source code file was modified since it was last accessed.
- URL—The URL consists of the following parts:
 - `https://`
 - `baseURL/` — In this tutorial, we assume that InterSystems IRIS is running on the server `devsys` and is using port `52773` so `baseURL` is `devsys:52773`
 - `api/atelier/` — This is defined by the web application that has the `%Api.Atelier` dispatch class.
 - URL part that identifies the method and target. This part can include fixed text and text that you specify to identify the namespace, document name, or type.

For example, the URL part that identifies the `GetDocNames` method is `v1/namespace/docnames/`. The complete URL for this method getting the documents from the MYNS namespace would be:

```
https://devsys:52773/api/atelier/v1/MYNS/docnames
```

The URL part that identifies the `GetServer` method is an empty string, so the complete URL for `GetServer` is:

```
https://devsys:52773/api/atelier/
```

- URL parameters — modifies the call. If the API method has URL parameters, they are described in the reference section.
- Inbound JSON payload — format of the inbound message for POST and PUT methods.
- Outbound JSON payload — format of the outbound message returned by the HTTP method.

Note: The endpoints for this API contain the term `atelier` because this API was developed for use by Atelier, our deprecated Eclipse-based IDE. Our VS Code - ObjectScript IDE now uses the same API.

2.2 Getting Information about the Server

Typically, the first REST call you'll make is to the [GetServer](#) method, which returns information about the InterSystems API version number and the namespaces available on the server.

```
GET https://devsys:52773/api/atelier/
```

This call returns the following JSON message:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": {
      "version": "IRIS for Windows (x86-64) 2018.1.1 (Build 515U) Mon Feb 5 2018 08:24:13 EST",
      "id": "98E1697E-13F9-4D6A-8B73-827873D1D61C",
      "api": 2,
      "features": [
        ...
      ],
      "namespaces": [
        "%SYS",
        "USER"
      ]
    }
  }
}
```

All the methods that return JSON messages use the same general format:

- status errors—typically the InterSystems IRIS Source Code File REST API returns errors as HTTP status codes. This field is used under some unusual conditions and this element contains the InterSystems IRIS %Status value, which may contain the text for multiple errors.
- status summary—contains a summary of the status errors.
- console—contains the text that InterSystems IRIS would display on the console for this operation.
- result—contains the results of the method.

The `GetServer` method returns information about the server in the “result” element. The result element contains one value “content”, which contains:

- version—contains the version string of the instance of InterSystems IRIS running on the server.
- id—contains the instance GUID of InterSystems IRIS.
- api—specifies the version number of the InterSystems IRIS Source Code File REST API implemented in this version of InterSystems IRIS.
- features—indicates the features that are enabled on this instance.

- namespaces—lists the namespaces defined on the InterSystems IRIS server.

The `GetNamespace` method returns information about the specified namespace, including the databases that are mapped to the namespace and a hash for each database. The hash is useful for improving efficiency of communication with the server. But you can get the information about the source code files in the namespace with just the namespace information returned by `GetServer`.

2.3 Getting the Source Code in a Namespace

To get the information about the source code files in a namespace:

- First you get the names of the files with the `GetDocNames` method.
- Then you get the contents of one file with the `GetDoc` method or you can get the contents of multiple files with the `GetDocs` method.
- If you want to improve the network efficiency of your application, you can keep a local cache of the names and contents of the source code files and use the `GetModifiedDocNames` method to get only the names of the source code files whose contents have changed or use the `GetDoc` method with the `If-None-Match` HTTP header.

The `GetDocNames` method returns the names of all of the source code files in all databases mapped to the namespace.

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": [
      {
        "name": "%Api.DocDB.cls",
        "cat": "CLS",
        "ts": "2016-08-03 20:01:42.000",
        "upd": true,
        "db": "IRISLIB",
        "gen": false
      },
      {
        "name": "EnsProfile.mac",
        "cat": "RTN",
        "ts": "2003-09-19 13:53:31.000",
        "upd": true,
        "db": "INVENTORYR",
        "gen": false
      },
      {
        "name": "xyz.mac",
        "cat": "RTN",
        "ts": "2016-08-11 15:05:02.167",
        "upd": false,
        "db": "INVENTORYR",
        "gen": false
      }
    ]
  }
}
```

The following `GetDoc` call returns the contents of the `xyz.mac` file:

```
https://devsys:52773/api/atelier/v1/INVENTORY/doc/xyz.mac
```

This call returns:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "xyz.mac",
    "db": "INVENTORYR",
    "ts": "2016-09-14 14:10:16.540",
    "upd": false,
    "cat": "RTN",
    "status": "",
    "enc": false,
    "flags": 0,
    "content": [
      "ROUTINE xyz",
      "xyz ;",
      "    w \"hello\""
    ]
  }
}
```

2.4 Creating a New File in a Namespace or Updating an Existing File

To create a new file in a namespace or update an existing file, you use the [PutDoc](#) method. For example, the following REST call creates a new xyz.mac source code file in the INVENTORY namespace or, if the xyz.mac file exists, this call replaces the original definition of the file with the new one. If you are updating a new file, you must specify either the HTTP header `If-None-Match` to identify the current version of the file or the `?ignoreConflict=1` URL parameter to bypass version checking. See [PutDoc](#) in the reference section for details.

```
PUT https://devsys:52773/api/atelier/v1/INVENTORY/doc/xyz.mac
```

You should specify the Content-Type `application/json` and the following JSON message:

```
{
  "enc": false,
  "content": [
    "ROUTINE xyz",
    "xyz ;",
    "    w \"hello\""
  ]
}
```

The call returns the following JSON message. It shows that the source code file has been created in the INVENTORYR database, which is the default database for routines in the INVENTORY namespace.

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "xyz.mac",
    "db": "INVENTORYR",
    "ts": "2016-09-14 14:10:16.540",
    "upd": false,
    "cat": "RTN",
    "status": "",
    "enc": false,
    "flags": 0,
    "content": []
  }
}
```

If you are updating or creating a binary file, specify a true value for `enc` and include the binary contents as an array of blocks of the base64 encoding of the binary value.

2.5 Compiling a File

The [Compile](#) method compiles the source code files specified by name in the incoming JSON array. For example, to compile `xyz.mac`, POST the following:

```
https://devsys:52773/api/atelier/v1/INVENTORY/action/compile
```

with the following JSON message:

```
[ "xyz.mac" ]
```

The method returns:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [
    "",
    "Compilation started on 08/14/2016 15:25:20 with qualifiers 'cuk'",
    "xyz.int is up to date. Compile of this item skipped.",
    "Compilation finished successfully in 0.008s."
  ],
  "result": {
    "content": []
  }
}
```

For some source code files, such as classes, `Compile` returns storage information in the returned content.

2.6 Deleting a File

The [DeleteDoc](#) method deletes the file specified in the URL. The `DeleteDoc` method has the same URL as the `GetDoc` method except that you use the HTTP Delete method instead of the Get Method. To delete `xyz.mac`, make an HTTP DELETE request with the URL:

```
https://devsys:52773/api/atelier/v1/INVENTORY/doc/xyz.mac
```

The Delete method returns the following JSON message:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "xyz.mac",
    "db": "INVENTORYR",
    "ts": "",
    "cat": "RTN",
    "status": "",
    "enc": false,
    "flags": 0,
    "content": []
  }
}
```

When a file has been deleted, the timestamp, `ts`, has a value of "" (empty string).

2.7 Performing an SQL Query

The `Query` method performs an SQL query on any InterSystems IRIS database. For example, if your application wants to present the user with a list of InterSystems IRIS roles, it can discover them with the following call:

```
POST https://devsys:52773/api/atelier/v1/%25SYS/action/query
```

With the SQL query specified in the incoming JSON message:

```
{"query": "SELECT ID,Description FROM Security.Roles"}
```

This call returns the results of the SQL query as JSON in the result content element.

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": [
      {
        "ID": "%all",
        "Description": "The Super-User Role"
      },
      {
        "ID": "%db_%default",
        "Description": "R/W access for this resource"
      },
      ...
      {
        "ID": "%sqltunetable",
        "Description": "Role for use by tunetable to sample tables irrespective of row level security"
      }
    ]
  }
}
```

You can use the `Query` method to query any table in InterSystems IRIS. For example, the following call queries a table named `Sample.Person` in a namespace named `SAMPLES`. The query requests a maximum of two records (`?max=2`) which meet the query criteria.

```
POST https://devsys:52773/api/atelier/v1/SAMPLES/action/query?max=2
{"query": "SELECT Age,SSN,Home_City,Name FROM Sample.Person WHERE Age = 25"}
```

This call returns:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": [
      {
        "Age": 25,
        "SSN": "230-78-7696",
        "Home_City": "Larchmont",
        "Name": "DeLillo,Jose F."
      },
      {
        "Age": 25,
        "SSN": "546-73-7513",
        "Home_City": "Gansevoort",
        "Name": "Klingman,Thelma H."
      }
    ]
  }
}
```

```
}  
  }  
}
```

The query API also supports the `positional` query parameter, which provides you the option to receive column metadata for each record in an array accompanying the record's content. For more information, refer to the class reference for `Query()`.

3

Source Code File REST API Reference

This page provides reference information on InterSystems IRIS® data platform Source Code File REST interface.

Note: The endpoints for this API contain the term `atelier` because this API was developed for use by Atelier, our deprecated Eclipse-based IDE. Our VS Code - ObjectScript IDE now uses the same API.

3.1 GetServer

This method returns information about the server, including the Source Code REST API version and namespaces that are available on the server.

For an example and additional details, refer to [Getting Information about the InterSystems IRIS Server](#).

3.1.1 URL

GET `https://<baseURL>/api/atelier/`

Where `<baseURL>` is the base URL for your instance.

3.1.2 JSON Messages

The following returned content is a server descriptor:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": {
      "version": "IRIS for Windows (x86-64) 2018.1.1 (Build 515U) Mon Feb 5 2018 08:24:13 EST",
      "id": "98E1697E-13F9-4D6A-8B73-827873D1D61C",
      "api": 2,
      "features": [
        ...
      ],
      "namespaces": [
        "%SYS",
        "USER"
      ]
    }
  }
}
```

3.1.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.2 HeadServer

This method returns the `HttpHeader` for the server.

3.2.1 URL

HEAD `https://<baseURL>/api/atelier/`

Where `<baseURL>` is the base URL for your instance.

3.2.2 JSON Messages

No returned content.

3.2.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.3 GetJobs

This method returns a list of running jobs on the InterSystems IRIS instance.

3.3.1 URL

GET `https://<baseURL>/api/atelier/v1/%25SYS/jobs`

Where `<baseURL>` is the base URL for your instance.

Note: Because `%` is a URL special character, to specify a literal `%` you must follow it with `25` (the hexadecimal code for the percent character). Therefore, you must use `%25SYS` to specify the literal `%SYS`.

3.3.2 JSON Messages

The following returned content is an array of job descriptors:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
```

```

"result": {
  "content": [
    {
      "pid": 1394,
      "namespace": "%SYS",
      "routine": "%Studio.Debugger.1",
      "state": "RUN",
      "device": "|TCP|1972|1394"
    },
    {
      "pid": 1345,
      "namespace": "%SYS",
      "routine": "RECEIVE",
      "state": "HANG",
      "device": "/dev/null"
    },
    {
      "pid": 1364,
      "namespace": "%SYS",
      "routine": "%SYS.TaskSuper.1",
      "state": "SELECTW",
      "device": "/dev/null"
    },
    {
      "pid": 1396,
      "namespace": "%SYS",
      "routine": "%SYS.cspServer3",
      "state": "READ",
      "device": "|TCP|1972|1396"
    },
    {
      "pid": 1346,
      "namespace": "%SYS",
      "routine": "ECPWork",
      "state": "RUNW",
      "device": "/dev/null"
    },
    {
      "pid": 1417,
      "namespace": "%SYS",
      "routine": "%SYS.BINDSRV",
      "state": "READ",
      "device": "|TCP|1972|1417"
    }
  ]
}

```

3.3.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.4 GetMetaData

This method returns the binary contents of the METADATA.zip file for the named database. Atelier uses this file to store index information so that it can preserve this information for future sessions.

3.4.1 URL

GET <https://<baseURL>/api/atelier/v1/%25SYS/metadata/database>

Where [<baseURL>](#) is the base URL for your instance.

Note: Because % is a URL special character, to specify a literal % you must follow it with 25 (the hexadecimal code for the percent character). Therefore, you must use %25SYS to specify the literal %SYS.

3.4.2 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 404 if the source code file does not exist.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.5 GetCSPApps

This method returns a list of web applications defined on the server or defined for a specified namespace on the server.

3.5.1 URL

GET `https://<baseURL>/api/atelier/v1/%25SYS/cspapps`

GET `https://<baseURL>/api/atelier/v1/%25SYS/cspapps/namespace`

Where:

<baseURL>

The base URL for your instance.

namespace

Specifies the name of the namespace. If *namespace* is not specified, this method returns the web applications for all namespaces.

Note: Because % is a URL special character, to specify a literal % you must follow it with 25 (the hexadecimal code for the percent character). Therefore, you must use %25SYS to specify the literal %SYS.

3.5.2 URL Parameters

The URL parameter `?detail=1` can be passed to return an array containing objects which describe the application in more detail.

3.5.3 JSON Messages

The following returned content is an array listing the defined web applications:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": [
      "/csp/broker",
      "/csp/documatic",
      "/csp/sys",
      "/csp/sys/exp",
      "/csp/sys/mgr",
      "/csp/sys/op",
      "/csp/sys/sec",
      "/isc/studio/rules",
      "/isc/studio/templates",
    ]
  }
}
```

```

    "/isc/studio/usertemplates",
    "/csp/user"
  ]
}

```

The following is the same returned content with detail=1:

```

{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": [
      {
        "name": "/csp/broker",
        "default": false
      },
      {
        "name": "/csp/documatic",
        "default": false
      },
      {
        "name": "/csp/sys",
        "default": true
      },
      {
        "name": "/csp/sys/exp",
        "default": false
      },
      {
        "name": "/csp/sys/mgr",
        "default": false
      },
      {
        "name": "/csp/sys/op",
        "default": false
      },
      {
        "name": "/csp/sys/sec",
        "default": false
      },
      {
        "name": "/isc/studio/rules",
        "default": false
      },
      {
        "name": "/isc/studio/templates",
        "default": false
      },
      {
        "name": "/isc/studio/usertemplates",
        "default": false
      },
      {
        "name": "/csp/user",
        "default": true
      }
    ]
  }
}

```

3.5.4 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.6 GetNamespace

This method returns information about a specific namespace.

3.6.1 URL

GET <https://<baseURL>/api/atelier/v1/namespace>

Where <baseURL> is the base URL for your instance.

3.6.2 JSON Messages

The following is the returned content information about the namespace USER:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": {
      "name": "USER",
      "db": [
        {
          "name": "USER",
          "crhash": "3A1A0E8B6C8",
          "default": true,
          "dbsys": false
        },
        {
          "name": "IRISLIB",
          "crhash": "A56AAA8D5418",
          "default": false,
          "dbsys": true
        },
        {
          "name": "IRISLOCALDATA",
          "crhash": "3A1A0551876",
          "default": false,
          "dbsys": false
        },
        {
          "name": "IRISSYS",
          "crhash": "3A19FFD2EF0",
          "default": false,
          "dbsys": true
        }
      ],
      "features": [
        {
          "name": "ENSEMBLE",
          "enabled": false
        }
      ]
    }
  }
}
```

3.6.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.7 GetDocNames

This method returns a list of source code file names. The optional *cat* and *type* constrain the types of source code files.

For an example and additional details, refer to [Getting the Source Code Files Defined in a Namespace](#).

3.7.1 URL

GET `https://<baseURL>/api/atelier/v1/namespace/docnames`

GET `https://<baseURL>/api/atelier/v1/namespace/docnames/cat`

GET `https://<baseURL>/api/atelier/v1/namespace/docnames/cat/type`

Where:

<baseURL>

The base URL for your instance.

cat

Specifies a category code: CLS = class; RTN = routine; CSP = CSP file (not recommended for use with InterSystems IRIS); OTH = other. Default is *.

type

Specifies a source code file type. Can be an * wildcard or a file type. For CLS, type must be *. For RTN, type may be mac, int, inc, bas ,mvi, or mvb. For CSP, type can be a list of file types such as js or css separated by commas. Default is *.

3.7.2 URL Parameters

- The URL parameter 'generated=1' specifies that generated source code files should be included.
- The URL parameter 'filter' provides a SQL filter that can be used to match the names.

3.7.3 JSON Messages

The following is the returned content, an array of source code file descriptors:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": [
      {
        "name": "%Api.DocDB.cls",
        "cat": "CLS",
        "ts": "2016-08-03 20:01:42.000",
        "upd": true,
        "db": "IRISLIB",
        "gen": false
      },
      ...
      {
        "name": "EnsProfile.mac",
        "cat": "RTN",
        "ts": "2003-09-19 13:53:31.000",

```

```
    "upd": true,
    "db": "INVENTORYR",
    "gen": false
  },
  ...
  {
    "name": "xyz.mac",
    "cat": "RTN",
    "ts": "2016-08-11 15:05:02.167",
    "upd": false,
    "db": "INVENTORYR",
    "gen": false
  }
]
}
```

3.7.4 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.8 GetModifiedDocNames

This method returns a list of source code files that have been modified since the time the databases had the specified hashes. It is passed a list of database keys and hashes as a JSON array. The hash values are used to determine if anything has changed in the database defined by the key. Typically, you first call this api with an empty array as the incoming JSON message. This returns the names of all source code files in the namespace with the database key and hash for each file. Then you can post the dbname and dbhash to discover which source code files have been modified on the server since the last call.

You post the list of source code files to check as shown in the following example:

```
[ { "dbname" : "USER",
  "dbhash" : "KWAGbOdnRblPzANaiv1Oiu0BZLI"
}, ... ]
```

3.8.1 URL

POST <https://<baseURL>/api/atelier/v1/namespace/modified/type>

Where:

<baseURL>

The base URL for your instance.

type

Specifies a source code file type as * or a three-letter code, ls, mac, int, inc, bas, or mvi. Default is *.

This call requires the header `Content-Type application/json`.

3.8.2 JSON Messages

The following is the returned content, an array of source code file descriptors:

```
[ { "dbname" : "USER",
  "dbhash" : "Qx1zuNaulq3b_1yR9ahZAfjkc-",
  "crhash" : "47763751EC",
  "docs": [ {
    "name": "User.NewClass1.cls",
    "ts": "2016-01-04 14:00:04.000",
    "gen": false,
    "depl": false
  }, ... ]
}, ... ]
```

If a source code file has been deleted since the specified dbhash, it is returned in the list with a time stamp set to an empty string:

```
"ts": ""
```

If a database was included because of mapping and the mapping is removed, both dbhash and crhash are returned with a "000" value and docs is returned as an empty array.

3.8.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 400 if the posted content is empty or *type* is anything other than CLS.
- HTTP 415 if content type is not application/json.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.9 PutDoc

This method saves the supplied source code file. If the file does not exist, this method creates it, and, if the file exists, this method replaces the existing file with the one specified. To ensure that you are overwriting the correct version of the file, specify the If-None-Match header with the timestamp value returned in the ETAG header of a previous PutDoc or GetDoc. If you want to overwrite the file without checking the version, specify the `?ignoreConflict=1` URL parameter. This method returns a corresponding source code file object. If you are saving a binary file, set the `enc` element of the incoming JSON message to true and include the file content as an array of blocks of base64. If the text on the server is changed during the save process (for example by a source control hook) the updated text will be returned in the content array of the returned source code file.

Errors pertaining to the source code file will be in the status property of the returned source code file object.

Version 2 PutDoc has the capability to accept the contents of the file in three formats: the default UDL format, XML format, and the format used by the legacy %RO export utility. PutDoc automatically recognizes the format of the file contents.

For an example and additional details, refer to [Creating a New File in a Namespace or Updating an Existing File](#).

3.9.1 URL and Input JSON Message

```
PUT https://<baseURL>/api/atelier/v1/namespace/doc/doc-name
```

```
PUT https://<baseURL>/api/atelier/v2/namespace/doc/doc-name
```

Where `<baseURL>` is the base URL for your instance.

The following is an example of the input JSON message for a PutDoc for the source code file xyz.mac:

```
{
  "enc": false,
  "content": [
    "ROUTINE xyz",
    "xyz ;",
    "  w \"hello\""
  ]
}
```

Note: If you are creating a CSP file (not recommended for InterSystems IRIS), the value of *doc-name* includes the / (slash) character. This is the reason that the URLMap defining PutDoc contains a (.) for this parameter name instead of :docname. See [Creating the URL Map for REST](#) for details.

3.9.2 URL Parameters

The URL parameter `?ignoreConflict=1` can be passed to bypass ETAG checking. This forces the source code file to be written to the server even if the file has changed since you previously accessed it.

3.9.3 HTTP Headers

- **If-None-Match**—To ensure that you are overwriting the correct version of the file, specify the If-None-Match header with the timestamp value returned in the ETAG header of a previous PutDoc or GetDoc.

3.9.4 JSON Messages

The following is the returned content for a PUT of source code file xyz.mac:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "xyz.mac",
    "db": "INVENTORYR",
    "ts": "2016-09-14 14:10:16.540",
    "upd": false,
    "cat": "RTN",
    "status": "",
    "enc": false,
    "flags": 0,
    "content": []
  }
}
```

When a class is saved PutDoc always returns the storage section because it may be normalized by the server. The 'flags' json field will be 1 if the contents is only the storage section. 'flags' will be 0 if PutDoc returns either the entire class in content or if content is empty.

3.9.5 HTTP Return Codes

- HTTP 200 if updated.
- HTTP 201 if created.
- HTTP 400 if the resource name is an invalid source code file name.
- HTTP 404 if the resource is not found.

- HTTP 409 if a conflict between server and client versions is detected based on the timestamp. If the file exists, PutDoc returns this code unless the If-None-Match header specifies the current timestamp value of the file on the server. If the conflict exists, the return message includes the contents of the source code file on the server.
- HTTP 415 if not passed application/json as content type.
- HTTP 425 if the source code file is locked and cannot be written to.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.10 GetDoc

This method returns the text for the named source code file and namespace.

Return content will contain a source code file object.

Errors pertaining to the source code file will be in the status property of the source code file object. If source control hooks are enabled for the namespace any console output generated by the hook will be captured and returned as an array of lines in the 'console' array.

The result contains the name of the requested file, the database where it is stored, its timestamp, and its category abbreviation (CLS = class; RTN = routine; CSP = CSP file [not recommended for use with InterSystems IRIS]; OTH = other), as well as the source code file contents which are returned in an array.

- For text files this will be an array of strings and the 'enc' json field will be set to false.
- For binary files this will be an array of base64 encoded chunks and the 'enc' field will be set to true.

Version 2 GetDoc can return the file contents in UDL format (the default), XML format, or the format used by the legacy %RO export utility.

For an example and additional details, refer to [Getting the Source Code Files Defined in a Namespace](#).

3.10.1 URL

```
GET https://<baseURL>/api/atelier/v1/namespace/doc/doc-name
```

```
GET https://<baseURL>/api/atelier/v2/namespace/doc/doc-name
```

Where `<baseURL>` is the base URL for your instance.

Note: If you are getting a CSP file (not recommended for use with InterSystems IRIS), the value of *doc-name* includes the / (slash) character. This is the reason that the URLMap defining GetDoc contains a (.*). See [Creating the URL Map for REST](#) for details.

3.10.2 URL Parameters

- The URL parameter `?binary=1` can be passed to force the source code file to be encoded as binary.
- The URL parameter `?storageOnly=1` can be passed to return only the storage portion of a class.
- In version 2, the URL parameter `?format=` parameter can be passed to specify that the contents of the file should be returned in UDL format (the default), XML format, or the format used by the legacy %RO export utility.
 - `?format=udl`
 - `?format=xml`

- ?format=%RO

If you specify ?binary=1, GetDoc ignores the format parameter.

3.10.3 HTTP Headers

- If-None-Match—Specify the value returned in the HTTP ETAG header from the previous call to GetDoc or PutDoc for this file. If the file has not changed since the previous call, GetDoc returns the HTTP 304 status.

3.10.4 JSON Messages

The following is an example of the first part of the result returned by requesting %Api.DocDB.cls:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "%Api.DocDB.cls",
    "db": "IRISLIB",
    "ts": "2016-09-13 22:31:24.000",
    "upd": true,
    "cat": "CLS",
    "status": "",
    "enc": false,
    "flags": 0,
    "content": [
      /// Routing class for the DocDB REST services",
      "Class %Api.DocDB Extends %DocDB.REST",
      "{",
      ...
    ]
  }
}
```

The following is the result of the same request with ?binary=1:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "%Api.DocDB.cls",
    "db": "IRISLIB",
    "ts": "2016-01-04 14:00:04.000",
    "cat": "CLS",
    "status": "",
    "enc": true,
    "content": [
      "Ly8vIFRoaxMgY2xhc3MgaXMgdGhlIHN1cGVyY2xhc3MgZm9yIGFsbCB1 ... PSAzIF0KewoKfQo="
    ]
  }
}
```

3.10.5 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 304 if the source code file has not been modified (see https://en.wikipedia.org/wiki/HTTP_ETag).
- HTTP 400 if the named resource is not a valid source code file name.
- HTTP 404 if the source code file does not exist.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

If a 'soft' error occurs such as a 'source code file does not exist', additional information can be found in the 'status' field of the result. Examples of other soft errors include 'file is locked'. For example, the following could be returned with an HTTP 404 return code:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "xyz1.mac",
    "db": "",
    "ts": "",
    "cat": "RTN",
    "enc": false,
    "content": "",
    "status": "ERROR #16005: Document 'xyz1.mac' does NOT exist"
  }
}
```

3.11 DeleteDoc

This method deletes the named source code file in the specified namespace. It returns the corresponding source code file object.

Errors pertaining to the source code file will be in the status property of the source code file object.

For an example and additional details, refer to [Deleting a File](#).

3.11.1 URL

DELETE <https://<baseURL>/api/atelier/v1/namespace/doc/doc-name>

Where [<baseURL>](#) is the base URL for your instance.

Note: If you are deleting a CSP file [not recommended for use with InterSystems IRIS], the value of *doc-name* includes the / (slash) character. This is the reason that the URLMap defining DeleteDoc contains a (*) for this parameter name instead of :docname. See [Creating the URL Map for REST](#) for details.

3.11.2 JSON Messages

The following is the returned content for a DELETE of source code file xyz.mac:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "name": "xyz.mac",
    "db": "INVENTORYR",
    "ts": "",
    "cat": "RTN",
    "status": "",
    "enc": false,
    "flags": 0,
    "content": []
  }
}
```

3.11.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 400 if the named resource is not a valid source code file name.
- HTTP 404 if the source code file does not exist.
- HTTP 423 if the resource is locked.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.12 HeadDoc

This method returns the `HTTPHeader` for the named source code file and namespace. This header contains a timestamp which can be used to detect discrepancies between server and client versions.

3.12.1 URL

HEAD `https://<baseURL>/api/atelier/v1/namespace/doc/doc-name`

Where `<baseURL>` is the base URL for your instance.

Note: If you are getting the HTTP header for a CSP file [not recommended for use with InterSystems IRIS], the value of `doc-name` includes the `/` (slash) character. This is the reason that the `URLMap` defining `HeadDoc` contains a `(.*)` for this parameter name instead of `:docname`. See [Creating the URL Map for REST](#) for details.

3.12.2 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 400 if the resource name is an invalid source code file name.
- HTTP 404 if the resource is not found.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.13 GetDocs

This method returns the text for all of the specified source code files in the namespace.

3.13.1 URL

POST `https://<baseURL>/api/atelier/v1/namespace/docs`

Where `<baseURL>` is the base URL for your instance.

A list of source code files to be fetched is passed in the body of the http request. The request body is a JSON array of names of source code files you want to fetch. For example, [`"%Api.DocDB.cls"`, ...].

This call requires the header `Content-Type application/json`.

3.13.2 JSON Messages

Return content is an array of source code file objects. See [GetDoc](#) method for an example of the structure of a source code file object.

Errors pertaining to a source code file will be in the status property of each source code file object. This method does NOT support the storageOnly flag. Neither does it do ETAG checking (and therefore will not return an HTTP 304 under any circumstances).

3.13.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 415 if the passed content type is not application/json.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.14 DeleteDocs

This method deletes a list of named source code files. It returns a corresponding array of source code file objects.

3.14.1 URL

DELETE `https://<baseURL>/api/atelier/v1/namespace/docs`

Where `<baseURL>` is the base URL for your instance.

The list of files to delete is passed in the body of the http request as a JSON array. For example, [`"%Api.DocDB.cls"`, ...].

This call requires the header `Content-Type application/json`.

3.14.2 JSON Messages

The following is the returned content for a DELETE of source code file `xyz.mac` and the nonexistent class `notexist.cls`:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [
  ],
  "result": [
    {
      "name": "xyz.mac",
      "db": "INVENTORYR",
      "status": ""
    },
    {
      "name": "notexist.cls",
      "db": "",
      "status": "ERROR #5001: Document Does Not Exist: User.notexist.cls"
    }
  ]
}
```

Errors pertaining to a each source code file will be in the status property of each returned source code file object. If the status is an empty string the source code file was deleted successfully. Otherwise the source code file was NOT deleted.

For deleted source code files, the db property will indicate from which database the doc was deleted.

3.14.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 400 if the posted data does not contain a JSON array.
- HTTP 415 if the passed content type is not application/json.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.15 Compile

This method compiles source code files. It permits the compilation of more than one source code file at a time. It returns an array of corresponding source code file objects.

The list of files to be compiled is passed in the body of the http request as a JSON array. For example, ["%Api.DocDB.cls", ...].

For an example and additional details, refer to [Compiling a File](#).

3.15.1 URL

POST `https://<baseURL>/api/atelier/v1/namespace/action/compile`

Where `<baseURL>` is the base URL for your instance.

This call requires the header `Content-Type application/json`.

3.15.2 URL Parameters

- The URL parameter 'flags' can be passed (default "cuk") which will be passed to the compiler.
- The URL parameter 'source' can be passed with a value of 0 if you don't want the source of the compiled source code file to be returned.

3.15.3 JSON Messages

The following is the returned content when compiling `Atelier.NewClass1`:

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [
    "Compilation started on 01/12/2016 17:44:00 with qualifiers 'cuk'",
    "Compiling class Atelier.NewClass1",
    "Compiling table Atelier.NewClass1",
    "Compiling routine Atelier.NewClass1.1",
    "Compilation finished successfully in 0.067s.",
    ""
  ],
  "result": {
    "content": [
```

```

{
  "name": "Atelier.NewClass1.cls",
  "status": "",
  "content": [
    "Storage Default",
    "{",
    "<Data name=\"NewClass1DefaultData\">",
    "<Value name=\"1\">",
    "<Value>%CLASSNAME</Value>",
    "</Value>",
    "</Data>",
    "<DataLocation>^Atelier.NewClass1D</DataLocation>",
    "<DefaultData>NewClass1DefaultData</DefaultData>",
    "<IdLocation>^Atelier.NewClass1D</IdLocation>",
    "<IndexLocation>^Atelier.NewClass1I</IndexLocation>",
    "<StreamLocation>^Atelier.NewClass1S</StreamLocation>",
    "<Type>%Storage.Persistent</Type>",
    "}",
    ""
  ],
  "db": "IRISSYS",
  "ts": "2016-01-12 17:44:00.053",
  "enc": false,
  "flags": 1
}
]
}
}

```

Errors pertaining to a source code file will be in the status property of each source code file object.

If compiling a persistent class causes the storage definition to change, the storage definition is returned as the content of a source code file object. Otherwise the result content will be empty.

3.15.4 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 400 if the resource name is an invalid source code file name.
- HTTP 404 if the resource is not found.
- HTTP 423 if the source code file is locked.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.16 Index

This method returns summary information on the specified source code files. Your application can use this information to create an index to the source code files. It returns an array of index source code file objects.

The list of source code files to be indexed is passed in the body of the http request. The request body is a JSON array of names of source code files. For example, ["%Api.DocDB.cls", ...].

3.16.1 URL

POST <https://<baseURL>/api/atelier/v1/namespace/action/index>

Where <baseURL> is the base URL for your instance.

This call requires the header `Content-Type application/json`.

3.16.2 JSON Messages

Errors pertaining to a source code file are in the status property of each source code file object. The returned array contains information relating to the structure and documentation of source code files on the server. It will vary by the category to which the source code file belongs. The following is an example for a class (category CLS). (Currently we only support the indexing of classes.):

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [],
  "result": {
    "content": [
      {
        "name": "%Activate.GenericObject.cls",
        "db": "IRISLIB",
        "ts": "2016-01-04 14:00:04.000",
        "gen": false,
        "others": [
          "%Activate.GenericObject.1.INT"
        ],
        "cat": "CLS",
        "content": {
          "desc": "This class provides functionality to create an ActiveX object, invoke its methods
and Get/Set its properties by name.",
          "depl": false,
          "depr": false,
          "final": false,
          "hidden": false,
          "super": [
            "%Activate.IDispatch"
          ],
          "methods": [
            {
              "name": "CreateObject",
              "desc": "This method is used to create a generic object given only its progid. If the
object cannot be found an exception is thrown.
The return value should be tested against $$$NULLLOREF in the usual manner to
ensure that the object has been successfully created",
              "depr": false,
              "final": true,
              "internal": false,
              "private": false,
              "scope": "class",
              "returntype": "%Library.RegisteredObject",
              "args": [
                {
                  "name": "Progid",
                  "type": "%Library.String"
                }
              ]
            },
            {
              "name": "GetObject",
              "desc": "This method is used to create a generic object from a moniker. If the object
cannot be found an exception is thrown.
The return value should be tested against $$$NULLLOREF in the usual manner to
ensure that the object has been successfully created.",
              "depr": false,
              "final": true,
              "internal": false,
              "private": false,
              "scope": "class",
              "returntype": "%Library.RegisteredObject",
              "args": [
                {
                  "name": "Moniker",
                  "type": "%Library.String"
                }
              ]
            }
          ]
        },
        "parameters": [],
        "properties": []
      },
      "status": ""
    ]
  }
}
```

```
} }  
}
```

3.16.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 415 if the passed content type is not application/json.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.17 Query

This method performs an SQL query on an InterSystems IRIS table and returns the results. The request body is a JSON object which specifies the query. It returns an array of objects that match the query conditions. Each returned object contains information relating to one row returned by the query. See the class reference for Query() for supported parameters.

3.17.1 URL

POST `https://<baseURL>/api/atelier/v1/namespace/action/query`

Where `<baseURL>` is the base URL for your instance.

The SQL query is specified in the body of the URL request. The query must specify a database in the specified namespace.

This call requires the header `Content-Type application/json`.

3.17.2 JSON Messages

Return content is an array of objects. Errors will be in the status property of each source code file object:

```
{  
  "status": {  
    "errors": [],  
    "summary": ""  
  },  
  "console": [],  
  "result": {  
    "content": [  
      {  
        "ID": "%all",  
        "Description": "The Super-User Role"  
      },  
      {  
        "ID": "%db_%default",  
        "Description": "R/W access for this resource"  
      },  
      {  
        "ID": "%db_irislocaldata",  
        "Description": "R/W access for this resource"  
      },  
      ...  
      {  
        "ID": "%sqltunetable",  
        "Description": "Role for use by tunetable to sample tables irrespective of row level security"  
      }  
    ]  
  }  
}
```

3.17.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 415 if the passed content type is not application/json.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.18 Search

This method finds files in the InterSystems IRIS database with the specified contents. The Search method is available in version 2 of the API. This method returns the results of the search in a format intended to be displayed to the user.

3.18.1 URL

POST `https://<baseURL>/api/atelier/v2/namespace/action/search`

Where `<baseURL>` is the base URL for your instance.

3.18.2 URL Parameters

- The required URL parameter `?query=expression` specifies a regular expression or a text string to search for in the specified files.
- The required URL parameter `?files=file-list` provides a comma-separated list of files or file masks, such as `al*.mac`, to search for the specified expression.
- The optional URL parameter `?regex=1` specifies that the query URL parameter contains a regular expression and is the default. `?regex=0` specifies that the query contains a text string and should not be interpreted as a regular expression.
- The optional URL parameter `?sys=1` specifies to include system files in the search. The default is `?sys=0`, which excludes system files.
- The optional URL parameter `?gen=1` specifies to include generated files in the search. The default is `?gen=0`, which excludes generated files.
- The optional URL parameter `?max=integer` specifies the maximum number of results to return. The default is `?max=200`.

3.18.3 JSON Messages

The following search REST call searches all `.cls` and `.mac` files for the word “Email” preceded and followed by a space. (In a regular expression, `\s` is matched by a space character.)

GET

`localhost:52773/api/atelier/v2/SAMPLES/action/search?query=.*\sEmail\s.*&files=*.cls,*.mac`

This call returns the following message. The return message may vary based on the contents of the SAMPLES namespace.

```
{
  "status": {
    "errors": [],
    "summary": ""
  },
  "console": [
    "",
    "Searching for '.*\\sEmail\\s.*' in '*.cls,*.mac'",
  ]
}
```

```

    "Wasabi.Data.Employee.cls(Email): Property Email ",
    "Wasabi.Person.API.Employee.cls(Email): Property Email ",
    "ZAUTHENTICATE.mac(175): Properties(\"EmailAddress\") - Email address",
    "Found 3 occurrence/s in 3 file/s."
  ],
  "result": [
    {
      "doc": "Wasabi.Data.Employee.cls",
      "matches": [
        {
          "member": "Email",
          "text": "Property Email "
        }
      ]
    },
    {
      "doc": "Wasabi.Person.API.Employee.cls",
      "matches": [
        {
          "member": "Email",
          "text": "Property Email "
        }
      ]
    },
    {
      "doc": "ZAUTHENTICATE.mac",
      "matches": [
        {
          "line": "175",
          "text": "Properties(\"EmailAddress\") - Email address"
        }
      ]
    }
  ]
}

```

3.18.4 HTTP Return Codes

- HTTP 200 if the request is valid.
- HTTP 400 if there are missing required URL parameters.

3.19 GetEnsClassType

This method returns a list of names of the classes meant for use in creating productions. You can specify the type of class to obtain, such as business service classes.

3.19.1 URL

GET <https://<baseURL>/api/atelier/v1/namespace/ens/classes/type>

Where:

<baseURL>

The base URL for your instance.

type

is an integer and returns classes corresponding to that integer as follows:

Adapters 1

InboundAdapters 2

OutboundAdapters 3

Messages 4
Requests 5
Responses 6
BusinessServices 7
BusinessProcesses 8
BusinessOperations 9
DataTransformation 10
Production 11
BusinessHost 12
Dashboard 13
Rule 14

3.19.2 JSON Messages

The following returned content is an array of class names:

```
{
  status: {
    errors: []
    summary: ""
  }
  console: []
  result: {
    content: [
      "Ens.Enterprise.MsgBank.BankTCPAdapter",
      "Ens.Enterprise.MsgBank.ClientTCPAdapter",
      "Ens.InboundAdapter",
      "Ens.OutboundAdapter"
    ]
  }
}
```

3.19.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

3.20 GetAdpInOutClass

This method returns the input and output type for a specified production adapter.

3.20.1 URL

GET <https://<baseURL>/api/atelier/v1/namespace/ens/adapter/name>

Where [<baseURL>](#) is the base URL for your instance.

3.20.2 JSON Messages

The following is an example of returned content:

```
{
  status: {
    errors: []
    summary: ""
  }
  console: []
  result: {
    content: {
      input: "%Stream.Object"
      output: "%String"
    }
  }
}
```

3.20.3 HTTP Return Codes

- HTTP 200 if OK.
- HTTP 404 if the adapter does not exist.
- HTTP 500 if an unexpected error occurred (details will be in status error array).

