



Adding Compiled Code to Customer Databases

Version 2023.1
2024-07-11

Adding Compiled Code to Customer Databases

InterSystems IRIS Data Platform Version 2023.1 2024-07-11

Copyright © 2024 InterSystems Corporation

All rights reserved.

InterSystems®, HealthShare Care Community®, HealthShare Unified Care Record®, IntegratedML®, InterSystems Caché®, InterSystems Ensemble®, InterSystems HealthShare®, InterSystems IRIS®, and TrakCare are registered trademarks of InterSystems Corporation. HealthShare® CMS Solution Pack™ HealthShare® Health Connect Cloud™, InterSystems IRIS for Health™, InterSystems Supply Chain Orchestrator™, and InterSystems TotalView™ For Asset Management are trademarks of InterSystems Corporation. TrakCare is a registered trademark in Australia and the European Union.

All other brand or product names used herein are trademarks or registered trademarks of their respective companies or organizations.

This document contains trade secret and confidential information which is the property of InterSystems Corporation, One Memorial Drive, Cambridge, MA 02142, or its affiliates, and is furnished for the sole purpose of the operation and maintenance of the products of InterSystems Corporation. No part of this publication is to be used for any other purpose, and this publication is not to be reproduced, copied, disclosed, transmitted, stored in a retrieval system or translated into any human or computer language, in any form, by any means, in whole or in part, without the express prior written consent of InterSystems Corporation.

The copying, use and disposition of this document and the software programs described herein is prohibited except to the limited extent set forth in the standard software license agreement(s) of InterSystems Corporation covering such programs and related documentation. InterSystems Corporation makes no representations and warranties concerning such software programs other than those set forth in such standard software license agreement(s). In addition, the liability of InterSystems Corporation for any losses or damages relating to or arising out of the use of such software programs is limited in the manner set forth in such standard software license agreement(s).

THE FOREGOING IS A GENERAL SUMMARY OF THE RESTRICTIONS AND LIMITATIONS IMPOSED BY INTERSYSTEMS CORPORATION ON THE USE OF, AND LIABILITY ARISING FROM, ITS COMPUTER SOFTWARE. FOR COMPLETE INFORMATION REFERENCE SHOULD BE MADE TO THE STANDARD SOFTWARE LICENSE AGREEMENT(S) OF INTERSYSTEMS CORPORATION, COPIES OF WHICH WILL BE MADE AVAILABLE UPON REQUEST.

InterSystems Corporation disclaims responsibility for errors which may appear in this document, and it reserves the right, in its sole discretion and without notice, to make substitutions and modifications in the products and practices described in this document.

For Support questions about any InterSystems products, contact:

InterSystems Worldwide Response Center (WRC)

Tel: +1-617-621-0700

Tel: +44 (0) 844 854 2917

Email: support@InterSystems.com

Table of Contents

Adding Compiled Code to Customer Databases.....	1
1 Requirements	1
2 Deploying Compiled Code	1
3 Limitations for DeployToFile() and InstallFromFile()	2
4 Example	2
5 Effect on Running Processes	2

Adding Compiled Code to Customer Databases

This page describes how to add compiled code to the customers' databases, so that you can provide your customers with new code that does not need to be recompiled.

Important: InterSystems highly recommends that you test this procedure with your specific classes in a test environment before using it on a live system.

1 Requirements

The requirements are as follows:

- The InterSystems IRIS® version must be the same on the system where you create and compile the code as it is on the system where you are installing it.
- The SQL delimited identifier setting must be the same on both systems.

2 Deploying Compiled Code

To deploy compiled code, do the following:

1. Create a project that contains class definitions, routines, and globals. To do so, use methods of the %Studio.Project class.
2. Make sure that all the code in the project has been compiled.
3. Obtain an OREF to the project, by using methods of %Studio.Project.
4. Call the **DeployToFile()** instance method of the project. For example:

ObjectScript

```
set sc=projectoref.DeployToFile("c:\test\myglobal.xml",,1)
```

Because the third argument is 1, the generated file does not contain the source code and intermediate code. The following shows the method signature and details:

```
method DeployToFile(file As %String,  
                  qspec As %String,  
                  removesource As %Boolean = 0) as %Status
```

Generates a file that contains the packaged code belonging to this project. *file* is the name of the file, and *qspec* is a string containing the standard compile qualifiers; see [Flags and Qualifiers](#). Note in particular that you should ensure that the `/exportselectivity` qualifier is specified as you want it. You can also specify the `k` flag, which controls whether the source code of generated routines is kept.

removesource is a boolean value. If *removesource* is 1, the global does not contain the routine and method sources, nor the intermediate code (regardless of the setting of the *k* flag).

For information on deployed mode, see [Putting Classes in Deployed Mode](#).

5. Provide this file to your customers with instructions. Customers should use the Terminal, switch to the appropriate namespace, and call the **InstallFromFile()** method of %Studio.Project, as follows:

```
set sc=##class(%Studio.Project).InstallFromFile("c:\test\myglobal.xml")
```

DeployToFile() automatically adds, to the list of items being deployed, any parent classes and any child classes referenced by relationships in this class.

3 Limitations for DeployToFile() and InstallFromFile()

The **DeployToFile()** and **InstallFromFile()** methods have the following limitations:

- The **DeployToFile()** and **InstallFromFile()** methods do not handle any class projections, for example, classes that project to Java files.
- These methods do not do any dependency checking and thus do not automatically include subclasses. It is your responsibility to insert all the classes you need into the package.

For example, **InstallFromFile()** does not check the location into which it installs the code. As an additional example, you could potentially deploy a subclass to a system that does not have the superclass installed.

Important: InterSystems highly recommends that you test this procedure with your specific classes in a test environment before using it on a live system.

4 Example

The following example shows a simple routine. Note that this routine creates a project but does not save it; there is no need to save the project before calling **DeployToFile()**.

```
; deployexample
set p=##class(%Studio.Project).%New()
do p.AddItem("Sample.Customer.cls")
do p.AddItem("Sample.Person.cls")

do p.DeployToFile("c:\test\myglobal.xml",,1)
```

For demonstration purposes, this simple routine does not include error checking.

5 Effect on Running Processes

This section describes the effect on any running processes when you load a new, compiled version of the code into a system where code is currently executing:

- Routines and class methods that are currently executing will continue to use the old code. If the routine or class method is called again from the same process after the compilation is complete, it will load the new code.

- If a routine or class method invokes another routine or class method and then returns to the caller, the process continues to use the old version of the calling code. For example, suppose that routine A invokes routine B, after which control returns to routine A. If you recompile routine A while routine A is running (or while routine B is running), when control returns to routine A, the process continues to use the old code for routine A.
- Any open process continues to use the in-memory version of any OREFs.
- Instance methods are dependent on an instance of an object. Any object will use the version of the instance methods that existed when the object was instantiated. The object will continue to use that code until the OREF is discarded and a new object is instantiated. So if you instantiate an object and then import a new version of the class (or delete it totally), you can still continue to call methods on the instance, which will use the version of the class that existed when the object was instantiated.

Note that you can query an OREF to see if the instance is using the latest version of the class code:

ObjectScript

```
Write oref.%ClassIsLatestVersion()
```

The `%ClassIsLatestVersion()` method returns 1 if the instance is using the latest version of the class code; otherwise it returns 0.

The preceding comments also apply when you recompile code in a given instance.

Note: The comments here apply on the instance where you are compiling the class. On another instance over ECP or an mirror member, the routine or class can briefly be inconsistent and can throw errors.

